

## SPECIFICATION SHEET: S027

### Aqua-Static Cubicle Range Systems One and Two



#### Detailed Product Specification

Materials and Design:	Cubicles designed to cope with the rigours of high use public change areas in a package suitable for wet and dry changing environments.
Doors and panels:	Compact / solid grade laminate, 12/13 mm thick, black core. All exposed edges smoothed and radiused.
Door Latch/Indicator Bolt:	Robust easy action door latch. Emergency exterior opening facility. Cubicle occupied indicator. Turn action ensures trouble free operation. Discreet security through fixings. Colour co-ordinated face and back plate. Vandal resistant design.
Door Hinge:	The solid grade laminate door is supported by a full length hinge bracket bonded and mechanically fixed top and bottom (middle fixing optional). Includes anti-finger trap and anti-lift design. Door can be adjustable to door open/close/ajar, and open inward or out.
Door:	Door closes against a full length sound deadening buffer. 20 mm gap between the header rail and the door top to eliminate finger trap. Door corners to be radiused.
Coat Hook:	Single aluminium coat hook with rubber safety buffer.
Sizes:	Cubicle sizes are tailored to suit your individual requirements. However, standard overall cubicle height is 1950 mm, 900-1000mm width, with 150 mm ground clearance.
Accessories:	Optional extra: Modesty panels, special fittings for disabled and family usage, baby change, wall panels etc.
Finish/Colour:	Doors and Panels: Extensive colour choice from any major laminate supplier in large sheet size. Frame extrusion/hardware/door furniture: Helmsman standard range – alternatively any other RAL colour requirement.
Frame extrusion/ Hardware/Door Furniture:	Aluminium polyester powder coated.
Cubicle Frame:	Unique fully framed; design manufactured from heavy gauge extruded aluminium, stabilises and strengthens unit. It is bonded and can be mechanically fixed to all panels. Header rail top fixing channels fitted with plastic insert strip.
Integral Leg:	Heavy-duty 150 mm high, providing 30 mm adjustment to accommodate uneven floors. Concealed floor fixings.
Seat:	Solid grade laminate (hardwood slat option available for dry areas), securely fitted on 3 sides with aluminium brackets. Optional fitting via 2 epoxy powder coated 'L' brackets, manufactured from 25 mm square section stainless steel. 10 mm gap spacing around all edges.
Installation:	Helmsman offers a full installation service for its products.

**HELMSMAN also provide an extensive range of lockers and changing room furniture.**

**After Sales Service:** All of our products are supported by the Helmsman Service Department who provide technical advice, maintenance schemes, prompt delivery of replacement keys/parts and product refurbishment.

- Health & Safety: Cubicles must be firmly secured to wall/floor and fixed together in runs for safety purposes. If applicable, install in accordance with specific product instructions.
- All dimensions are nominal.
- To enable us to interpret your requirements accurately, please state at time of enquiry/order the choice of colour and delivery requirement.
- The products described in this specification sheet herein are the subjects of patent, trademark, design and copyright protection or application thereof.
- In the interest of efficiency and service to our customers, the company reserves the right to modify the specifications of any of its products without prior notice.

