

***SPECIFICATION SHEET: S081***  
***SYSTEM 1300HD HEAVY DUTY RANGE***  
***1-6 COMPARTMENT LOCKERS***



**Nominal Dimensions:**

Height	Width	Depth
1775 mm	300 mm	300 mm
1775 mm	300 mm	450 mm
1775 mm	380 mm	380 mm
1775 mm	380 mm	450 mm
1775 mm	450 mm	450 mm

***Strength and Security with Style***

Sturdy Construction:	Door frame constructed from heavy gauge mild steel of press formed channel section.
Door Strength:	Manufactured from 10mm thick solid grade laminate or compact density fibreboard in a plant on style. Supported as standard by unsprung semi-concealed "five knuckle", 180° opening, hinges.
Style:	Attractive and functional locker design.
Colour:	We have a wide range of modern colours and finishes available from several leading manufacturers in the UK; please ask for details from the sales department.

***Detailed Product Specification***

Nesting:	Lockers are supplied as single units.
Construction:	Spot welded and pop riveted.
Door Frame Assembly:	Comprising two uprights manufactured from heavy gauge mild steel of press formed channel section. Spot welded construction produces a rigid frame enabling door clearances to be maintained in accordance with British Standard requirements.
Doors:	Solid grade laminate or Compact Density Fibreboard doors are attached to the right hand side of door frame upright with semi-concealed unsprung five knuckle 180° hinges.
Bottom:	The bottom is formed as a 60 mm high plinth. All edges have return bends and the front and rear edges drilled for fitting to stands or stands with seat.
Shelf:	The one compartment locker is fitted with a shelf 315 mm from the top, giving a clear 250 mm opening, allowing adequate space for the average crash helmet with chin protector, or other articles.
Hook & Hanger Rails:	A coat hook is located each side of the main compartment (for one and two compartment lockers) under the shelf; for lockers over 300 mm deep a plastic coated clothes hanger rail is also fitted.
Locking:	Standard options are either 10 disc tumbler cam lock in mastered suite with two keys to each lock or, at no extra cost, a latch lock for the user's own padlock (recommended padlock shank dimensions 6 mm). Recommended padlocks are available from Helmsman.

Colour Range: We have a variety of finishes and colours from several leading manufacturers; please ask for details from our sales department.

**OPTIONAL EXTRAS:** The following can be supplied at an additional cost and, if included, will be specified in the quotation.

Hinges: An option of a sprung 'five knuckle' semi-concealed self closing hinges giving 180° door opening can be applied at an additional cost.

Fire Retardant: Standard laminate achieves the Euroclass rating of C or BS Class 1, we can provide fire retardant (FR) laminate which is Euroclass B or Class 0. This is subject to an additional charge.

Compact Density Fibreboard is fire-rated as Euroclass B or Class 0.

(Our powder coating material on the mild steel carcass, also achieves the BS Class 0.)

Shelves: Shelves can be added in compartments if required.

Combination Lock: The standard cam lock or latch lock can be replaced with a door-mounted combination lock with master key over-ride facility and user codes which can be reset.

Refund/Collect Lock: Coin operated lock optionally available. Its master keyed user access by key on pin or wristband using coin or token specified. Accepts most European coins.

Locker Numbering: **1:** Each compartment can be supplied with a plastic oval number plate recessed into the door centrally positioned at the top of the door. Maximum amount of digits is 4.

**2:** Each compartment can be supplied with a number engraved into the door centrally positioned at the top of the door. Maximum amount of digits is 4.

Stands/Stands with Seats: Lockers can be provided with either stands or stands with seats with or without adjustable feet. Please refer to Specification Sheet S015.

Sloping Tops: Lockers can be manufactured with a sloping top. Gradient 1:3, ie  
300 mm deep unit increased height at rear 100 mm  
380 mm deep unit increased height at rear 126 mm  
450 mm deep unit increased height at rear 150 mm  
550 mm deep unit increased height at rear 183 mm

End Panels: For aesthetic appearance and to protect row ends, specifically designed end panels are available.

Installation: Helmsman offers a full installation service for its products.

**Bespoke:** We have the ability to customise our products to meet your requirement and space, providing solutions for awkward corners, uneven floors or even curved walls. **After-sales Service:** All of our products are supported by the Helmsman Service team who provide technical advice, maintenance schemes, prompt delivery of replacement keys/parts and product refurbishment. Contact them on 01284 727633 or email [service@helmsman.co.uk](mailto:service@helmsman.co.uk)

- Health & Safety: Lockers must be firmly secured to wall or floor and fixed together in runs for safety purposes. If applicable, install in accordance with specific product instructions.
- All dimensions are nominal.
- To enable us to interpret your requirements accurately, please state at time of enquiry/order the choice of locker type, colour, locking and nesting arrangement and delivery requirement.
- The products described in this specification sheet herein are the subjects of patent, trademark, design and copyright protection or application thereof.
- In the interest of efficiency and service to our customers, the company reserves the right to modify the specifications of any of its products.

